VisionLine RWC





Technical specifications:

Housing	Material Colour Dimensions	Aluminium Red/bronze mat (anodized) Ø88mm x ca. 209mm (incl. ball joint mounting, in case of direct wall-mounting)
Joint	Material Mech. adjustment range	Stainless steel Tilt angle up to 90° Rotation angle approx. 360°
Protective hose	Material Length	Stainless steel (AISI-316L) approx. 1 m
Camera	Sensor Video size Video interface View angle	CMOS 1080P@60Hz; 1080P@50Hz HDMI 90° (optional 142°)
Operating voltage	Supply voltage Rated current Max. current	24 V DC 0,4 A 2,1 A
LED (8x)	Colour temperature Light intensity Luminous flux Efficiency	5000 K 28000 mcd 26 lm 103 lm/W
Additional	Protection class Weight	IP64* approx. 3,5 kg (total weight including protective hose)

* only when system is under pressure with a minimum of 0,3 bar

VisionLine RWC

R00000.50.00



Scope of delivery:

- Camera with rotating inspection glass
- Ball joint mounting
- Stainless steel hose 1 m
- Assembly seal (+replacement)
- HDMI-repeater-coupling
- Compressed air connector Ø6mm
- M12 plug 5-pole A-coded
- Fine filter unit 3-stages



Replacement assembly seal

Fine filter unit, 3-stages







VisionLine RWC

R00000.50.00

